




Read the operating instructions prior to commissioning

# FlexFusion® ELECTRIC PLATINUM COMBI TEAM



## Installation manual

### Model

FPDE615.615  
FPDE615.621  
FPDE621.615  
FPDE621.621  
FPDE115.615  
FPDE115.621  
FPDE121.615  
FPDE121.621  
FPDE615.115  
FPDE621.115  
FPDE615.115  
FPDE621.121



Henny Penny Corporation  
P.O.Box 60  
Eaton, OH 45320  
USA

Phone +1 937 456-8400  
Fax +1 937 456-8402

Toll free in USA  
Phone +1 937 417-8417  
Fax +1 937 417-8434

[www.hennypenny.com](http://www.hennypenny.com)

<b>1 Introduction .....</b>	<b>5</b>
<b>1.1 About this manual .....</b>	<b>5</b>
1.1.1 Explanation of signs .....	6
<b>1.2 Personnel qualifications .....</b>	<b>7</b>
<b>1.3 Use of the unit .....</b>	<b>7</b>
<b>1.4 Warranty .....</b>	<b>7</b>
<b>2 Safety instructions .....</b>	<b>8</b>
<b>3 Description of the unit .....</b>	<b>10</b>
<b>3.1 Overview of the unit .....</b>	<b>10</b>
<b>3.2 Unit and connection data .....</b>	<b>10</b>
<b>4 Transporting the unit .....</b>	<b>16</b>
<b>4.1 Transporting the unit to the installation site .....</b>	<b>16</b>
<b>4.2 Unpacking the unit .....</b>	<b>17</b>
<b>5 Installing the unit .....</b>	<b>18</b>
<b>5.1 Minimum clearances .....</b>	<b>18</b>
<b>5.2 Lifting the unit off the pallet .....</b>	<b>19</b>
<b>5.3 Installing the unit on the unit legs .....</b>	<b>20</b>
<b>5.4 Aligning the unit .....</b>	<b>21</b>
<b>5.5 Fastening the unit to the floor .....</b>	<b>21</b>
5.5.1 Securing the unit to prevent tipping .....	21
5.5.2 Unit on casters: Attach both castor stops to the floor .....	24
<b>5.6 Unit on casters: Secure device to the wall .....</b>	<b>24</b>
<b>6 Connecting the unit .....</b>	<b>26</b>
<b>6.1 Opening and closing the housing .....</b>	<b>26</b>
6.1.1 Removing and attaching the side wall .....	26
<b>6.2 Making the electrical connection .....</b>	<b>27</b>
6.2.1 Connecting the electrical connection line .....	29
6.2.2 Connecting the power optimization system .....	31
6.2.3 Connecting the potential equalization .....	32
<b>6.3 Connecting the kitchen guiding system .....</b>	<b>32</b>
<b>6.4 Making the basic setting of the control .....</b>	<b>34</b>
6.4.1 Changing the basic setting of the control .....	34
<b>6.5 Making the water connection .....</b>	<b>35</b>
6.5.1 Connecting the drinking water connection line .....	36
6.5.2 Connecting softened drinking water to both connections .....	36
<b>6.6 Making the wastewater connection .....</b>	<b>37</b>
6.6.1 Connecting the waste water line to a permanent connection .....	38
<b>6.7 Making the exhaust air connection .....</b>	<b>39</b>
6.7.1 Connecting the exhaust air line .....	39

<b>7 Checking the function .....</b>	<b>40</b>
7.1 Checking the controls .....	40
7.2 Checking the inspection of the cooking chamber door .....	40
7.3 Heating and rinsing the unit .....	41
<b>8 Putting the unit into service .....</b>	<b>42</b>
8.1 Filling out the Start-up operation report .....	42
8.2 Nameplate .....	45

# 1 Introduction

## 1.1 About this manual

The installation instructions are part of the unit and contain information on safe installation of the unit.

Observe the following notes and adhere to them:

- Read the installation instructions completely prior to installation.
- Make the installation instructions available to the installation fitter at the operating site at all times.
- Preserve the installation instructions throughout the service life of the unit.
- Insert any additions from the manufacturer.
- Pass on the installation instructions to any subsequent operator of the unit.

**Target group** The target group of the installation instructions is trained qualified personnel that is familiar with installing and operating the unit.

**Figures** All figures in this manual are intended as examples. Discrepancies can arise between this and the actual unit.

### 1.1.1 Explanation of signs

---

#### **DANGER**

##### **Imminent danger**

Failure to comply will lead to death or very severe injuries.

---

#### **WARNING**

##### **Potential danger**

Failure to comply can lead to death or very severe injuries.

---

#### **CAUTION**

##### **Dangerous situation**

Failure to comply can lead do slight to moderately severe injuries.

---

#### **NOTICE**

##### **Property damage**

Failure to comply can cause property damage.

---

#### **INFORMATION**

##### **Information**

Notes for better understanding and operation of the unit.

---

Symbol / sign	Meaning
•	Listing of information.
→	Action steps which can be performed in any sequence.
1. 2.	Action steps which must be performed in the specified sequence.
↳	Result of an action performed or additional information relating to it.

## 1.2 Personnel qualifications

### Explanation of qualification

Skilled personnel	<ul style="list-style-type: none"> <li>• A skilled person is someone who, on the basis of their technical training, knowledge and experience as well as familiarity with the applicable standards, can assess the assigned work and recognize possible dangers.</li> </ul>
-------------------	--

Type of activity	Qualification
Electrical connection	<ul style="list-style-type: none"> <li>• Electrician</li> <li>• Specialized training</li> <li>• Employee of the responsible technical company</li> </ul>
Water connection	<ul style="list-style-type: none"> <li>• Water specialist</li> <li>• Specialized training</li> <li>• Employee of the responsible technical company</li> </ul>
Waste water connection	<ul style="list-style-type: none"> <li>• Waste water specialist</li> <li>• Specialized training</li> <li>• Employee of the responsible technical company</li> </ul>

## 1.3 Use of the unit

This unit is intended to be used solely for commercial purposes, particularly in commercial kitchens.

## 1.4 Warranty

The warranty is void and safety is no longer assured in the event of:

- Improper conversion or technical modifications of the unit,
- Improper use,
- Improper startup, operation or maintenance of the unit,
- Problems resulting from failure to observe these instructions.

## 2 Safety instructions

The unit complies with applicable safety standards. Residual risks associated with operation or risks resulting from incorrect operation cannot be ruled out and are mentioned specifically in the safety instructions and warnings.

The installation fitter must be familiar with regional regulations and observe them.

The installation fitter must observe the safety instructions in these installation instructions and in the "Safety information" chapter of the operating instructions.

### **Ensuring conformity with standards**

Observe applicable international, European and national laws, regulations, standards and directives for the unit when transporting, setting up and connecting it.

### **Improper installation**

#### **Risk of property damage and personal injury from improper installation**

- Install the unit only as specified in these installation instructions.
- Do not add anything to the unit or modify the unit.
- Use only original spare parts.

### **Transportation and storage**

#### **Risk of personal injury and property damage from improper transportation and improper storage**

- Store the unit in a dry, frost-free environment.
- Observe the safety regulations for the lifting gear used.
- Attach the unit to the lifting gear securely during transport and installation, and prevent it from dropping.
- Transport the unit in an upright position, do not tilt or stack.
- Pay attention to protruding parts when transporting the unit without packaging.

### **Fire prevention**

#### **Risk of fire from combustible surfaces**

- Observe general fire prevention regulations.

### **Organizational measures**

#### **Risk of property damage and personal injury from lack of organizational measures**

- Identify danger zones when transporting, installing and connecting the unit.
- Prior to starting the installation tasks, notify any operator present about the procedure.
- Prior to starting the installation task, discuss how to behave in an emergency.
- Use equipment and protective gear suitable for the activity.
- Brace housing components to prevent them from falling over and dropping.



**Installation Risk of property damage and personal injury from improper installation**

- Ensure that the installation area has adequate load-bearing capacity.
- Wear safety shoes and protective gloves.

**Electrical connection Risk of fire from improper connection**

- Observe applicable regional regulations of the electric supplier.
- Ensure that only electricians licensed by the electric supplier connect the unit.
- Ensure that the electrical system is earthed by a protective earthing conductor.
- Note the information on the nameplate.

**Danger of electric shock from live components.**

- Prior to working on the electrical system, switch off the unit, disconnect the electrical system from the mains and prevent power from being switched on again. Check to ensure the system is dead.
- Use only insulated tools.

**Unit on casters or rollers Danger from the supply line tearing off with units on casters or rollers**

- The securing device must be designed for a tensile load of at least 0.6 kN.
- The safety cable must be shorter than the connection line of the unit.
- Do not mount casters under a standard base frame with adjustable legs.

**Commissioning Risk of property damage and personal injury from improper commissioning**

- Read the operating instructions prior to commissioning. Observe the safety instructions in these installation instructions and in the "Safety information" chapter of the operating instructions.
- Only put the unit into service after a successful function test in its assembled state.
- Put the unit into service only after it has reached room temperature.
- Observe the units during operation.

### 3 Description of the unit

#### 3.1 Overview of the unit




Image: Floor-standing unit

- a Hang-in frame

b Insulating disk

c Door handle

d Cooking chamber door

e Lighting (door)

f Water drainage channel (door)

g Water drainage channel (cooking chamber)

h Cooking chamber

i USB port (covered)

j Unit leg
- k Rack

l Nameplate

m Hand shower

n Supply air opening

o Operating unit

p Housing

q Air inlet nozzle

r Steam outlet nozzle

#### 3.2 Unit and connection data

FlexiCombi Team

Size	615-615 615-621	621-621 621-615	115-615 115-621 615-115 621-115	121-615 121-621 615-121 621-121
Dimensions				

Size	615-615 615-621	621-621 621-615	115-615 115-621 615-115 621-115	121-615 121-621 615-121 621-121
Unit Length x Width x Height (mm (in))	997 (39,25) x 799 (31,46) x 1700 (66,93)		997 (39,25) x 799 (31,46) x 1900 (74,8)	
Dimension of unit on castors				
Unit Length x Width x Height (mm (in))	1152 (45,35) x 1009 (39,72) x 1700 (66,93)		1152 (45,35) x 1009 (39,72) x 1900 (74,8)	
Weight				
Unit ≈ (kg (lb))	253 (557,9)		291 (641,7)	
Weight of unit on castors				
Unit ≈ (kg (lb))	271 (597,6)		309 (681,3)	

## INFORMATION

- All voltages listed below are technically available.
- For some voltages, however, the implementation must be agreed with the manufacturer.
- The voltage for which the device is designed is indicated on the nameplate.

Size	615	621	115	121
Emissions				
Noise level (db(A))	< 70			
Steam output (g/h (oz/h))	2760 (97,35)	5540 (195,41)	4210 (148,5)	8080 (285,01)
Steam output (m³/h (cuft/h))	4,7 (165,9)	9,4 (331,7)	7,1 (250,5)	13,7 (483,4)
Latent heat dissipation (W)	1872	3762	2862	5490
Sensible heat dissipation (W)	1248	2508	1908	3660
With condensation hood				
Steam output (g/h (oz/h))	830 (29,28)	1660 (58,55)	1260 (44,44)	2430 (85,71)
Steam output (m³/h (cuft/h))	1,4 (49,4)	2,8 (98,8)	2,1 (74,1)	4,1 (144,7)
Latent heat dissipation (W)	562	1129	859	1647
Sensible heat dissipation (W)	1248	2508	1908	3660
The sensible and latent heat amounts are determined in Germany on the basis of VDI 2052 at a connection voltage of 400 V. The applicable regional regulations may vary from this.				
Operating environment				
Temperature (°C (°F))	5 (41 ) — 40 (104 )			
Relative humidity (%) non-condensing	95			
Cooking chamber light				
Light source	LED module			
Electrical connection				
Protective system	IPX5			

## Description of the unit

Size	615	621	115	121
Type of connection	3NPE / AC 50/60 Hz, 3PE / AC 50/60 Hz			
<b>Voltage (V)</b>	<b>200</b>			
Connected load (kW)	10.1	16.3	14.7	25.5
Fuse (A)	3 x 35	3 x 50	3 x 50	3 x 80
<b>Voltage (V)</b>	<b>208</b>			
Connected load (kW)	10.2	17.4	15.7	27.3
Fuse (A)	3 x 35	3 x 50	3 x 50	3 x 80
<b>Voltage (V)</b>	<b>220</b>			
Connected load (kW)	11.6	19.7	17.7	30.8
Fuse (A)	3 x 35	3 x 63	3 x 63	3 x 100
<b>Voltage (V)</b>	<b>230</b>			
Connected load (kW)	12.6	21.4	19.3	33.6
Fuse (A)	3 x 35	3 x 63	3 x 63	3 x 100
<b>Voltage (V)</b>	<b>240</b>			
Connected load (kW)	13.7	23.3	21	36.5
Fuse (A)	3 x 35	3 x 63	3 x 63	3 x 100
<b>Voltage (V)</b>	<b>380</b>			
Connected load (kW)	9.4	18.9	14.4	27.6
Fuse (A)	3 x 16	3 x 35	3 x 25	3 x 50
<b>Voltage (V)</b>	<b>400</b>			
Connected load (kW)	10.4	20.9	15.9	30.5
Fuse (A)	3 x 16	3 x 35	3 x 25	3 x 50
<b>Voltage (V)</b>	<b>415</b>			
Connected load (kW)	11.2	22.5	17.1	32.8
Fuse (A)	3 x 16	3 x 35	3 x 25	3 x 50
<b>Voltage (V)</b>	<b>440</b>			
Connected load (kW)	10.4	20.9	15.8	30.5
Fuse (A)	3 x 16	3 x 35	3 x 25	3 x 50
<b>Voltage (V)</b>	<b>480</b>			
Connected load (kW)	12.3	20.9	18.9	32.6
Fuse (A)	3 x 16	3 x 35	3 x 25	3 x 50
<b>Softened drinking water connection</b>				
Water type	Softened drinking water, cold			
Temperature (°C (°F))	< 30 (86 )			
Residual hardness CaCO <sub>3</sub> (mmol/l (ppm))	< 1 (100 ppm)			
Chloride Cl (mg/l)	< 100			
Iron Fe (mg/l)	< 0.2			

Size	615	621	115	121
Connection pressure (kPa (psi))	200 (29) — 600 (87)			
Connection (")	R 3/4			
Drinking water connection				
Water type	Drinking water, cold			
Temperature (°C (°F))	< 30 (86 )			
Carbonate hardness CaCO <sub>3</sub> (mmol/l (ppm))	< 4 (400 ppm)			
Connection pressure (kPa (psi))	200 (29) — 600 (87)			
A pressure reducer must be installed upstream in the following countries: Denmark, Sweden, Norway, Finland.				
Connection (")	R 3/4			
Water consumption, steaming				
Softened drinking water (l/h (gal/h))	16 (4,23)	21 (5,55)	18 (4,76)	24 (6,34)
Water consumption, combisteaming				
Softened drinking water (l/h (gal/h))	3,5 (0,92)	4,6 (1,22)	4 (1,06)	5,3 (1,4)
Water consumption, WaveClean cleaning program				
Softened drinking water (l (gal))	3 l (0,79)			
Drinking water (l (gal))	32 l (8,45)			
Waste water connection				
Waste water type	Dirty water, maximum 80 °C (176 °F)			
Connection to unit (mm (in))	50 (1,97)			
Maximum length (m (ft))	1 (3,3) with downward slope of at least 5% or 3°			
Temperature resistance (°C (°F))	95 (203 )			
Maximum flow rate (l/min (gal/min))	10 (2,64)			
Exhaust air connection				
Connection to unit (mm (in))	53 (2,09)			
Maximum length (m (ft))	2,5 (8,2)			
Temperature resistance (°C (°F))	180 (356)			
If both cooking chambers are used at the same time, the values given in the individual columns are added together.				

### Fastening to the floor

Absolutely essential for the following unit types
FPDE115-615
FPDE115-621
FPDE121-615
FPDE121-621

## Description of the unit

### Transformer voltage

Type of connection	3NPE / AC 50/60 Hz, 3PE / AC 50/60 Hz	
Voltage range (V)	208 — 240	
Transformer	T1	
Wire identification or color	blue	red
Voltage measured (V)	Voltage at transformer (V)	
208	0	208
240	0	240

### Basic setting of the control

Basic setting	Parameters	Standard value	Range of adjustment	Explanation
Supply voltage	14	400	100 — 500 V	Enter the local, mean voltage between the line conductors.
Date / time			yyyy - mm - dd	Year - Month - Day
			hh : mm	Hour : Minute
Altitude	2	0 — 999	0 — 999 m (3277 ft)	Request the altitude above sea level from the local weather station. If the altitude is unknown, enter 0 — 999 m (3277 ft).
			1000 m (3280 ft) — 1999 m (6557 ft)	
			2000 m (6560 ft) — 2499 m (8197 ft)	
			2500 m (8200 ft) or higher	
Volume of audible signal		Medium	Individual	Sets the volume.
Temperature unit setting	1	°C	°C	Celsius (°C)
			°F	Fahrenheit (°F)
Volume unit	34	ml	(ml)	Milliliter (ml)
			(fl.oz.)	Fluid ounce (fl.oz.)
	35	Imperial (fl.oz.)	Imperial (fl.oz.)	Imperial fluid ounces
			U.S. (fl.oz.)	U.S. fluid ounces
Water filter maintenance	44	0	0 — 99900 l (26393,66 gal)	Water quantity up to the maintenance message.
				0 = No maintenance message
Network		DHCP	Network address and DHCP	Select and set interface.

Basic setting	Parameter s	Standard value	Range of adjustment	Explanation
Kitchen control technology	652	Disabled	0 = Disabled 1 = Active	Indicates whether the kitchen guiding system is in use.
	659	Ethernet	0 = Ethernet 1 = Serial	Type of signal transmission (interface)
	653	1188	0 — 65535	TCP port setting
	654	254	0 — 254	Unit address
80 % power	3	100	80 % 100 %	Power can be limited to 80 % (for special applications).
Energy optimization system (Performance optimization system)	42	Off	On Off	If an energy optimization system is connected, "On" must be selected to allow the unit to heat.
Settings parameters				<ol style="list-style-type: none"> <li>1. Set parameters via the roller.</li> <li>2. Tap the "Read" button to display the set values.</li> <li>3. Specify another value via the button panel.</li> <li>4. Press the "Write" button to save the new value.</li> </ol>

### Basic setting of control (Advanced)

Basic setting	Parameter s	Standard value	Range of adjustment	Explanation
Generator mode	45	0	0 = No 1 = Yes	When a generator is used to supply electricity
HoodIn (Wrase deletion)	48	1	0 = Lower water consumption, large amount of steam in the unit when the cooking chamber door is opened 1 = Normal 2 = Higher water consumption, greatly reduced amount of steam in the unit when the cooking chamber door is opened	Setting of the strength of the vapour quenching. Depending on the setting, cooking method and cooking product, water consumption may be increased.
Time format	675	0	0 = 24 h 1 = 12 h	Set the 12-h or 24-h time format
Format for cooking program times	676	0	0 = hh:mm 1 = mm:ss 2 = automatic	Display format for cooking program times

## 4 Transporting the unit

### ⚠ CAUTION

#### Risk of property damage and personnel injury from tipping unit

- Stay clear of lifted unit.
- Move lifted unit carefully.

### ⚠ CAUTION

#### Risk of property damage and personnel injury from tipping unit

- Do not drive the unit with casters to the installation site on the casters.  
⇒ Only move the unit to the installation site using a suitable means of transport.

### NOTICE

#### Risk of property damage from improper transport

- Transport the unit upright.
- Do not tilt or stack the unit.
- Pay attention to protruding parts when transporting the unpacked unit.

Prior to transporting the unit to the installation site, ensure that:

- The roadway has adequate load-bearing capacity.
- Wall openings are large enough.

### 4.1 Transporting the unit to the installation site




Image: Lengthwise and crosswise transport on pallet

→ Use suitable transport means to move unit to its installation site.



## 4.2 Unpacking the unit

### CAUTION

#### Risk of injury from sharp edges

- Wear protective gloves.


### INFORMATION

When unpacking the unit, inspect it for transport damage.

Do not install damaged units or put into service.


1. Remove the packaging.
2. Pull the protective film off the unit.
3. Remove all packaging material from the cooking chamber.
4. Clean the unit (See Operating instructions).
5. Enter the information from the nameplate into the Start-up operation report.
6. Enter the information from the nameplate into the Operating instructions.

## 5 Installing the unit

 **WARNING**

**Risk of burns from spraying hot fat**


- Install deep-fat fryers outside the range of the hand shower.

 **WARNING**

**Danger of the unit tipping over on casters**


If the unit is tilted on casters, it may tip over and seriously injure you.

- Do not tip the unit on casters.

 **CAUTION**


**Risk of crushing from improper installation**

- Protect the unit and work area during installation and alignment.

 **CAUTION**

**Risk of fire from failure to observe applicable regional fire prevention regulations**

- Observe applicable regional fire prevention regulations.

 **NOTICE**

**Risk of property damage from overheating of the unit**

- Do not install the unit close to heat sources.

### 5.1 Minimum clearances




Image: Minimum clearances to walls, ceiling or units

A	B	C *	D **
50 (1,97)	100 (3,94)	---	50 (1,97)
All dimensions in mm (in)			

A	B	C *	D **
* Depends on the kitchen ventilation system and quality of ceiling material			
** For service work 500 mm (19,69 in) recommended			

The following clearances from walls, ceilings or other equipment must be maintained when installing the unit:

- Left, right and rear at least 50 mm (1,97 in).
- For service work, left 500 mm (19,69 in) recommended.
- Distance to heat sources (oven), left 500 mm (19,69 in).
- Clearance to deep-fat fryers, at least one length of the hand shower at left and right.




Image: Minimum distance from equipment with high heat radiation on right and left side.

## NOTICE

### Material damage to the device control due to excessive ambient temperatures

Minimum distance to equipment with large heat radiation 510 mm (20") on right and left side.

These include, for example:

- Gas stoves
- Gas griddle plates
- Grills
- Deep fryers

## 5.2 Lifting the unit off the pallet

### ⚠ CAUTION

#### Risk of property damage and personnel injury from tipping unit

- Stay clear of lifted unit.

- Move lifted unit carefully.

### NOTICE

#### Risk of property damage from lifting the unit incorrectly

- Place the forks of the pallet truck next to the siphon.

Additional support at the rear side of the unit is required to lift it safely.

#### Requirement for additional support for the unit

- Square metal profile at least 40 x 40 x 2 mm.
- Alternatively, a piece of timber of 40 x 40 mm can be used.




Image: Lifting the unit off the pallet

#### Prerequisite Unit unpacked

Protective film removed

Unit cleaned

The rear side support is present

Parking brakes of the casters locked

1. Slide the forks of the pallet truck under the unit and to the right of the siphon.
2. Place the rear side support of the unit on the forks of the pallet truck.
3. Slightly raise the forks and make sure that the rear side support does not shift and that it is securely in contact with the unit.
4. Carefully lift the unit off the pallet.

## 5.3 Installing the unit on the unit legs

#### Prerequisite The floor must support the weight of the unit

1. Use appropriate lifting gear to lift the unit.
2. Install the unit in accordance with the planning drawing.

3. Align the unit lengthwise and crosswise (see "Aligning the unit").

## 5.4 Aligning the unit




Image: Installing the unit on the unit legs

### INFORMATION

For units on castors, balance the unit by placing washers between the castor and the frame.

1. Place a bubble level on the unit.
2. Align the unit horizontally by screwing the unit legs in or out.
3. Fill out the start-up operation report.

## 5.5 Fastening the unit to the floor

### 5.5.1 Securing the unit to prevent tipping

#### **WARNING**

#### **Risk of accident from insufficient fastening**

Unit can tip over

- Depending on the unit type, suitable measures must be taken to fasten the unit to the floor.
- Comply with the requirements for the condition of the floor.
- Comply with the requirements for the means of fastening.
- Follow the manufacturer's instructions for using the means of fastening.

Depending on the size, it is essential that certain combisteamer types or combisteamers used in combination with a Stapelkit (stacking kit), a recirculation hood, an underframe or base cabinet be secured to prevent tipping.

Unit types that must be secured to prevent tipping (see "Unit and connection data").




Image: Arrangement of the floor plates (view from above)

- a Cooking chamber door
- b Unit leg or underframe
- c Floor plates

To prevent the unit from tilting, a special fastening kit is supplied by the manufacturer or is available as an accessory.

The fastening kit contains two floor fasteners and all components required to bolt or bond to the floor.

The unit or underframe is fastened by means of two floor fasteners as shown in the drawing.

### Floor without steam barrier

In the case of floors without a steam barrier, the floor plates are bolted to the floor using the bolts provided.




Image: A: Position of floor plate; B: floor plate bolted to the floor

- a Cap nut
- b Holding plate
- c Upright bolt
- d Floor plate
- e Lag bolt
- f Unit leg

**Prerequisite** Floor capable of accommodating the weight of the unit  
 Floor must be clean and suitable for the manner fastening  
 Unit set up and aligned in accordance with the planning drawing

1. Insert the floor plate from the fastening kit into the retainer as shown in the drawing.
2. Screw on the cap nuts hand-tight.
3. Align the floor fastener in position 1-1 or 2-2 on the unit leg or underframe as shown in the drawing and mark the fastening holes on the floor.
4. Mark the position of all unit legs or underframe on the floor.
5. Using suitable lifting equipment, move the unit so that the holes can be drilled in the floor.
6. Drill holes with a diameter matching that of the anchor sufficiently deep in the floor.
7. Carefully place the unit in the installation position.
8. Screw on cap nuts and remove the retainer from the floor plate.
9. Using the anchors and fastening screws provided, screw the floor plate to the floor.
10. Ensure that a tight seal against the floor has been reestablished after the fastening screws are installed.
11. Place retainer on the floor plate and secure using cap nuts.
12. Complete the start-up operation report.

## Floor with steam barrier

In the case of floors with a steam barrier, the floor plates are not screwed to the floor but fastened with the enclosed adhesive.




Image: A: Position of floor plate; B: floor plate glued to the floor

- a Cap nut
- b Holding plate
- c Upright bolt

- d Floor plate
- e Unit leg

**Prerequisite** Floor capable of accommodating the weight of the unit  
Floor must be clean and suitable for the manner fastening  
Unit set up and aligned in accordance with the planning drawing

1. Insert the floor plate from the fastening kit into the retainer as shown in the drawing.
2. Screw on the cap nuts hand-tight.
3. Align the floor fasteners in position 1-1 or 2-2 on the unit leg or underframe as shown in the drawing and mark the floor.
4. Screw on cap nuts and remove the retainer from the floor plate.
5. Using the adhesive provided, fasten the floor plates to the floor.
  - ↳ Follow the manufacturer's instructions regarding the adhesive.
  - ↳ Apply the adhesive in accordance with the manufacturer's instructions.
  - ↳ Observe the drying time specified in the manufacturer's instructions.
6. Place retainers on the floor plates and secure using cap units.
7. Complete the start-up operation report.

### 5.5.2 Unit on casters: Attach both castor stops to the floor

**Prerequisite** Floor capable of accommodating the weight of the unit  
Floor must be clean and suitable for the manner fastening

1. Place the unit in the intended position.
2. Place caster stops on the rear casters.
3. Mark the position of the caster stops on the floor.
4. Remove the unit.
5. Fix the caster stops to the floor using the appropriate material for the floor in question.
6. Observe the manufacturer's specifications for the fastening material.

### 5.6 Unit on casters: Secure device to the wall

**Prerequisite** Wall must be designed for a tensile force of at least 0.6 kN.  
The safety rope for securing must be shorter than the connecting cables of the device.

1. Place the unit in the intended position and in the casters stops.
2. Guide the arresting wire to the wall to determine the correct position of the wall mounting.
  - ↳ Safety rope and wall mounting are not part of the scope of delivery.
3. Mark the position of the wall mounting.
4. Fix the wall mounting to the wall using the material suitable for the wall in question.
5. Observe the manufacturer's specifications for the fastening material.



6. After completing the work, check the safety function.

## 6 Connecting the unit

### DANGER

#### Risk of personal injury and property damage from electric shock

- Prior to working on the **FlexiCombi Team**, ensure that the **two** electrical circuits inside the unit are de-energized.
- Do not operate the unit with the housing open.

### CAUTION

#### Risk of injury from sharp edges

- Wear protective gloves.

### NOTICE

#### Risk of property damage from damage to the lines

- Remove and attach housing components carefully.

## 6.1 Opening and closing the housing

### 6.1.1 Removing and attaching the side wall

#### Removing the side wall




Image: Removing the side wall

1. Unscrew the bolts in the center of the side wall.
2. Unscrew the bolts at the bottom of the side wall.
3. Pull the bottom edge of the side wall forwards.
4. Remove the side wall.

#### Attaching the side wall

### NOTICE

#### Risk of property damage from leaky housing

- Check gaskets when attaching the housing parts.

- Replace damaged gaskets.

1. Insert top edge of side wall.
2. Carefully push the bottom of the side wall inward.
3. Secure the bottom of the side wall with bolts.
4. Secure bolts at the center of the side wall.
5. Check that the side wall is in contact with the unit on all sides.

## 6.2 Making the electrical connection

### Electrical installation work

Electrical installation work on the electric system and the unit may only be performed by a specialist company, which is approved by the electric utility company in the particular region. The applicable regional regulations, standards and guidelines must be observed, as well as the connection conditions imposed by the electric utility company responsible.

### Technical qualifications for electrical installation tasks

Electrical installation tasks on the electrical system and the unit may be carried out only by an electrician provided by the specialist company contracted.

The unit must be connected in accordance with the information on the nameplate and the instructions of this manual.

### Wiring diagram

The wiring diagram is included with the unit.

The wiring diagram and additional documents are available on the manufacturer's Internet page by entering the serial number of the unit (see Imprint).

### Electrical connection line

Minimum requirements for the unit's electrical connection line to the electrical supply mains:

Connection	Electrical connection line
Permanent connection for fixed installation with a cable from the unit to a separate connection box.	Rubber sheath cable, oil-resistant, shrouded and flexible in accordance with IEC 60245-57 (for example: H05RN-F).
Connection of the unit with a connector.	
Permanent connection for fixed installation with a hard-wired line directly connected to the unit.	PVC sheathed cable for permanent installation in buildings or damp and wet rooms.

### Permanent connection

#### CAUTION

#### Risk of property damage and personal injury from improper installation

- In the case of a fixed electrical connection, install an all-pole disconnecting unit with at least 3 mm (0.12 in) contact opening in front of the unit.

Install an all-pin separating device if the unit will be connected permanently to the electrical supply mains.

#### CAUTION

#### Risk of property damage and personal injury from improper installation

- The plug-in connection must be readily accessible.

### Plug-in connection

If the unit is connected with a plug to the electrical supply mains, use plugs and sockets according to IEC60309.

The socket must be readily accessible so that the unit can be disconnected from the electrical supply mains at any time.

---

## INFORMATION

Each unit must be connected individually.

Do **not** join the connection lines.

### Insulation monitoring

In the case of an unearthed network (IT network), the unit can be incorporated into the insulation monitoring.

### Fault current device




Image: RCD switch type A circuit symbol

The unit can be connected to a fault current device.

If a residual-current circuit breaker is used, the residual-current circuit breaker installed must be type A (RCD type A ) to ensure that AC fault currents and pulsating DC fault currents are detected.

If the unit is connected to electrical supply mains without a neutral conductor, a type B fault current circuit breaker (RCD type B), which is sensitive to all types of current, must be installed.

The unit generates a small fault current through use of special electronic components. To ensure that the residual current device does not trip during normal operation, each unit should have its own residual current device.

### Potential equalization




Image: Potential equalization symbol

The unit can be included in a potential equalization system by means of appropriately sized wiring.

## 6.2.1 Connecting the electrical connection line

### DANGER

#### Risk of personal injury and property damage from electric shock

- Prior to working on the **FlexiCombi Team**, ensure that the **two** electrical circuits inside the unit are de-energized.
- Do not operate the unit with the housing open.

### DANGER

#### Risk of personal injury and property damage from electric shock

- Before connecting, ensure that the electrical connection line is dead.
- Ensure that the electrical connection line is undamaged.




Image: Connecting the electrical connection line

- |                        |                              |
|------------------------|------------------------------|
| a Connection terminals | c Electrical connection line |
| b Cable tie            | d Threaded cable connection  |

## INFORMATION

Each unit must be connected individually.

Do **not** join the connection lines.

**Prerequisite** Unit disconnected from power supply

Electrical connection line dead

Unit adjusted to supply voltage

Side wall open

1. Feed the electrical connection line into the unit through the threaded cable connection.
2. Connect the power connection cable in accordance with the wiring diagram.
3. Secure the electrical connection line with cable ties.
4. Tighten the threaded cable connection securely to provide strain relief.
5. Close the housing (see "Opening and closing the housing").
6. Fill out the Start-up operation report.

## 6.2.2 Connecting the power optimization system

The unit can be connected to a power optimization system with a potential-free contact. The potential-free contact is used to link the unit to the control.

### DANGER

#### Risk of personal injury and property damage from electric shock

- Prior to working on the **FlexiCombi Team**, ensure that the **two** electrical circuits inside the unit are de-energized.
- Do not operate the unit with the housing open.

### DANGER

#### Risk of personal injury and property damage from electric shock

- Before connecting, ensure that the electrical connection line is dead.
- Ensure that the electrical connection line is undamaged.

### INFORMATION

When integrating the device into an power optimization system, observe the information in the operating manual of the power optimization system.

### INFORMATION

Each unit must be connected individually.

Do **not** join the connection lines.

#### Prerequisite Unit dead

Connection line dead

Housing opened

1. Pull the electrical connection line into the unit through the cable gland.
2. Route the electrical connection line to the connection terminals.
3. Connect connection cable in accordance with the circuit diagram.
4. Secure connection cable with cable tie.
5. Log on the power optimization system in the basic control setting (see "Making the basic control setting").
6. Complete the start-up operation report.

6.2.3 Connecting the potential equalization




Image: Connecting the potential equalization

INFORMATION

Perform this procedure separately for each unit.

- 1. Route and connect the potential equalization line to the marked connection.
- 2. Fill out the Start-up operation report.

6.3 Connecting the kitchen guiding system

The units can be connected to a kitchen guiding system using an RJ45 plug.

 **DANGER**

Risk of personal injury and property damage from electric shock

- Prior to working on the **FlexiCombi Team**, ensure that the **two** electrical circuits inside the unit are de-energized.
- Do not operate the unit with the housing open.

Minimum requirements for the network cable

Type of network	Ethernet
Cable quality	4-pair shrouded patch cable Cat-5 S/FTP
Connection to unit	Shrouded RJ45 connector






Image: Connecting the kitchen guiding system

- |                  |                 |
|------------------|-----------------|
| a RJ45 socket    | d Network cable |
| b RJ45 connector | e Ferrite ring  |
| c Cable tie      |                 |

## INFORMATION

Perform this procedure separately for each unit.

**Prerequisite** Unit dead  
Housing opened

1. Pull the network cable into the unit through the cable gland.
2. Route the network cable through the two ferrite rings, with one winding through each.
3. Connect the network cable to the unit with the RJ45 connector.
4. Register the network in the basic control setting (see "Making the basic control setting").
5. Fill out the Start-up operation report.

### 6.4 Making the basic setting of the control




Image: Main menu

- |   |   |
|---|---|
| a <i>Standby</i> button                 | f "WaveClean" fully automatic cleaning button |
| b Information strip                     | g "Unit functions" button                     |
| c Help button                           | h "myFavorites" favorite button               |
| d "manualCooking" manual cooking button | i "autoChef" automatic cooking button         |
| e Language selection button             |   |

#### 6.4.1 Changing the basic setting of the control

By entering the password "2100", the basic setting for the installation can be displayed and changed.

---

#### INFORMATION

The basic settings are made in the dialogue.

Advanced settings are made via the parameters for the settings.

---

---

#### INFORMATION

Perform this procedure separately for each unit.

---

**Prerequisite** Unit is on

The Main menu is displayed

1. Tap the "Unit functions" button.  
↳ The *Unit functions* menu is displayed.
2. Tap the "Unit settings" field.  
↳ The *PIN* window opens.
3. Enter the password.

4. Tap the *Confirm* button.
  - ↳ The *Unit settings* menu is displayed.
  - ↳ The basic settings can be changed (see "Unit and connection data").
5. Fill out the Start-up operation report.

## 6.5 Making the water connection

### Drinking water installation tasks

Drinking water installation tasks on drinking water lines and the unit may only be performed by a specialist company, which is approved by the drinking water utility company in the particular region. The applicable regional regulations, standards and guidelines must be observed, as well as the connection conditions imposed by the drinking water utility company responsible.

### Technical qualifications for drinking water installation tasks

Drinking water installation tasks on drinking water lines and the unit may be carried out only by a water specialist provided by the specialist company contracted.

The unit has a connection for permanent installation to the drinking water supply.

The unit is equipped with a permanent connection for:

- Softened drinking water for steam generation
- Drinking water for cooling, rinsing and cleaning

### CAUTION

#### Hygiene risk from contaminated drinking water

- The connection to the drinking water network must be equipped with a type EA backflow preventer.

### NOTICE

#### Risk of property damage from the wrong water quality

- Ensure that the water quality complies with the unit and connection data.

### INFORMATION

The unit can be connected to a reverse osmosis system.

The material of the connection line from the reverse osmosis system to the unit must be suitable.

### INFORMATION

Always connect both water connections to the unit.

### 6.5.1 Connecting the drinking water connection line

#### INFORMATION

Each unit must be connected individually.

Do **not** join the connection lines.

**Prerequisite** Water pressure complies with specifications (see "Unit and connection data")  
Backflow preventer installed  
Pressure-resistant connection lines suitable for tap water are available

1. Connect the connection lines to the drinking water taps using seals.
2. Flush the connection lines thoroughly.
3. Insert dirt filters into the water connections on the unit.
4. Connect the drinking water connection line to the unit.
5. Connect the connection line for softened drinking water to the unit.
6. Open the tap water valves and check the threaded connectors for leaks.
7. Fill out the Start-up operation report.




Image: Water connection

- |                           |                                      |
|---------------------------|--------------------------------------|
| a Connection line         | d Backflow preventer                 |
| b Softened drinking water | e Softened drinking water connection |
| c Drinking water          | f Drinking water connection          |

### 6.5.2 Connecting softened drinking water to both connections

If only softened drinking water is available at the installation site, use a T-piece to connect both water connections on the unit to each other.

## INFORMATION

Each unit must be connected individually.

Do **not** join the connection lines.

**Prerequisite** Water pressure complies with specifications (see "Unit and connection data")  
 Backflow preventer installed  
 Pressure-tight connection line suitable for drinking water is available

1. Connect the connection line to the tap for softened drinking water using a seal.
2. Flush the connection line thoroughly.
3. Insert dirt filters into the water connections on the unit.
4. Connect T-piece to the unit.
5. Connect the connection line for softened drinking water to the T-piece using a seal.
6. Open the drinking water tap and check the threaded fittings for leakage tightness.
7. Fill out the Start-up operation report.




Image: Connecting softened drinking water to both connections

- |                           |               |
|---------------------------|---------------|
| a Backflow preventer      | d T-piece     |
| b Softened drinking water | e Seal        |
| c Connection line         | f Dirt filter |

## 6.6 Making the wastewater connection

### Waste water installation tasks

Waste water installation tasks on waste water systems and the unit may only be carried out by a specialized company that is responsible for waste water systems. The applicable regional regulations, standards and guidelines must be observed, as well as the connection conditions imposed by the operator of the waste water company responsible.

### Technical qualifications for waste water installation tasks

Waste water installation tasks on waste water lines and the unit may be carried out only by a waste water specialist provided by the specialist company contracted.

#### 6.6.1 Connecting the waste water line to a permanent connection

##### NOTICE

##### Overflow of the device through an externally mounted siphon

Combi steamers have an integrated siphon.

An additional, external siphon without ventilation of the drain line will cause the unit to overflow in these combi steamers.

Therefore, do not connect an external siphon without ventilation to the waste water connection.

The wastewater connection needs a free outlet or vent.

Only exception:

- FlexFusion Gold **without WaveClean**

##### INFORMATION

If a siphon is installed in the waste water system, a vacuum breaker must be installed in the waste water line.




Image: A Permanent connection without siphon, B Permanent connection with siphon provided on site

- a Waste water connection
- b Waste water line
- c Waste water mains

- d Siphon on waste water mains
- e Pipe clamp
- f Vacuum breaker

## INFORMATION

Each unit must be connected individually.

Do **not** join the connection lines.

**Prerequisite** The waste water line complies with the specifications (see "Unit and connection data")

1. Install waste water line up to connection to the waste water system.
2. Secure waste water line with pipe clamps.
3. Fill the siphon of the unit with drinking water.
4. Fill out the Start-up operation report.

## 6.7 Making the exhaust air connection

When installing the unit under a ventilation system, observe the regional regulations for air conditioning systems.

### NOTICE

#### Risk of property damage from fouling of the outgoing air ducts

- Not connect the exhaust airline directly to the ventilation system.

### NOTICE

#### Risk of corrosion damage from condensate

- Install the exhaust air line such that condensate cannot collect.

### 6.7.1 Connecting the exhaust air line




Image: Connecting the exhaust air line

**Prerequisite** The exhaust air line complies with the specifications (see "Unit and connection data")

1. Connect the exhaust air line to the steam outlet nozzle.
2. Route exhaust air line to the ventilation system with a 3° rise.
3. Fasten the end of the exhaust air line 50 mm (1,97 in) — 200 mm (7,87 in) underneath the ventilation system.
4. Fill out the Start-up operation report.

## 7 Checking the function

### DANGER

**Risk of personal injury and property damage from unsuccessful operational check**

- Do not put the unit into service.
- Contact customer service.

---

### INFORMATION

Perform this procedure separately for each unit.

**Prerequisite** Electrical connection made  
Water connection made  
Waste water connection made  
Unit aligned  
Unit cleaned

### 7.1 Checking the controls

1. Switch on the unit and start any cooking program (see operating instructions).
  - ↳ Set the cooking chamber temperature to a higher temperature than the current cooking chamber temperature.
  - ↳ The unit heats up.
  - ↳ Once the set temperature is reached, heating switches off.
  - ↳ The temperature no longer increases.
  - ↳ The controls are functioning.
2. Switch off the unit.
3. Fill out the Start-up operation report.

### 7.2 Checking the inspection of the cooking chamber door

1. Switch on the unit and start any cooking program (see operating instructions).
  - ↳ The unit heats up.
  - ↳ The fan is turning.
2. Open the cooking chamber door during operation.
  - ↳ The unit shuts off the heating function.
  - ↳ The fan comes to a stop.
  - ↳ The monitoring of the cooking chamber door is functioning.
3. Close the cooking chamber door.
4. Switch off the unit.
5. Fill out the Start-up operation report.



## 7.3 Heating and rinsing the unit

1. Switch on the unit.
2. Tap the "Manual cooking" button.  
↳ The Manual cooking menu is displayed.
3. Steam cooking mode for 15 minutes at 100 °C (212 °F).
4. Rinse the cooking chamber thoroughly with clear water.
5. Operate hot air cooking mode for 5 minutes at 180 °C (356 °F).
6. Open the cooking chamber door and leave it ajar until the unit is used again.
7. Complete the start-up operation report.

## 8 Putting the unit into service

### INFORMATION

If the unit is not put into service immediately after being connected and the function check, all inspections must be repeated.

- Prerequisite**
- Electrical connection made
  - Water connection made
  - Wastewater connection made
  - Exhaust air connection made (if required by the customer)
  - Function checked successfully
  - Housing closed
1. Instruct operator.
  2. Fill out the Start-up operation report.

### 8.1 Filling out the Start-up operation report

General information	Yes	No
Enter the data on the nameplate. SN: _____ Type _____ Electrical connection _____ Designation _____ Item no.: _____ (if available)		
Obvious damage to the device? What and where? _____	<input type="checkbox"/>	<input type="checkbox"/>
Unit levelled?	<input type="checkbox"/>	<input type="checkbox"/>

General information	Yes	No		
Is it necessary to secure the device against tipping or slipping? If so, how was it secured?	<input type="checkbox"/>	<input type="checkbox"/>		
<table border="0"> <tr> <td> <b>secured against tipping</b>  <input type="checkbox"/> Screwed to floor  <input type="checkbox"/> Glued to floor </td> <td> <b>secured against shifting</b>  <input type="checkbox"/> Screwed to floor  <input type="checkbox"/> Glued to floor </td> </tr> </table>	<b>secured against tipping</b> <input type="checkbox"/> Screwed to floor <input type="checkbox"/> Glued to floor	<b>secured against shifting</b> <input type="checkbox"/> Screwed to floor <input type="checkbox"/> Glued to floor		
<b>secured against tipping</b> <input type="checkbox"/> Screwed to floor <input type="checkbox"/> Glued to floor	<b>secured against shifting</b> <input type="checkbox"/> Screwed to floor <input type="checkbox"/> Glued to floor			

Electrical connection	Yes	No
Electrical connection made properly?	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> Potential equalization	<input type="checkbox"/> power optimization plant (LOA)	
<input type="checkbox"/> Potential-free contact	<input type="checkbox"/>	
Electrical connections made properly?	<input type="checkbox"/>	<input type="checkbox"/>
Fault current protection installed immediately upstream of this unit?	<input type="checkbox"/>	<input type="checkbox"/>

Kitchen guiding system	Yes	No
Kitchen guiding system connected properly?	<input type="checkbox"/>	<input type="checkbox"/>

Basic control setting	Yes	No
Set temperature unit		
<input type="checkbox"/> °C <input type="checkbox"/> °F		
Date and time set?	<input type="checkbox"/>	<input type="checkbox"/>
current software version _____		
set installation altitude		
<input type="checkbox"/> 0 — 999 m (3277 ft) <input type="checkbox"/> 1000 m (3280 ft) — 1999 m (6557 ft)		
<input type="checkbox"/> 2000 m (6560 ft) — 2499 m (8197 ft) <input type="checkbox"/> 2500 m (8200 ft) or higher		
80% power set?	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> 100 % <input type="checkbox"/> 80 %		
Voltage set in the control.		
Voltage: _____ V		
Audible signal volume set?	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> Low <input type="checkbox"/> High		
Signal tone selected?	<input type="checkbox"/>	<input type="checkbox"/>
Set volume unit		
<input type="checkbox"/> ml <input type="checkbox"/> fl.oz. (Imperial)		
<input type="checkbox"/> fl.oz. (U.S.)		
Is the energy optimization system (Performance optimization system) set?	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> On <input type="checkbox"/> Off		
Set water filter maintenance		
<input type="checkbox"/> No maintenance message <input type="checkbox"/> maintenance message at _____ l (gal)		
Network configuration set?	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> DHCP IP address: _____		
Subnet mask: _____ Gateway: _____		
Kitchen guiding system set?	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> Active <input type="checkbox"/> Disabled		
<input type="checkbox"/> Ethernet <input type="checkbox"/> Serial		
TCP port: _____ Unit address: _____		
Unit address: _____		

Water connection	Yes	No
Connection pressure within indicated range?	<input type="checkbox"/>	<input type="checkbox"/>
Connection pressure: _____ ( _____ ) kPa (psi)		
Water connection made properly?	<input type="checkbox"/>	<input type="checkbox"/>

## Putting the unit into service

Water connection	Yes	No
Lines and connections leak-tight?	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> Connected only to softened drinking water <input type="checkbox"/> Connected only to drinking water		
Water connections connected with T-piece?	<input type="checkbox"/>	<input type="checkbox"/>

Waste water connection	Yes	No
Waste water connection made in a technically correct manner?	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> Siphon in the building <input type="checkbox"/> Vacuum breaker		
<input type="checkbox"/> Funnel drain <input type="checkbox"/> Floor drainage channel		
Diameter of the drain pipe: _____ mm (in)		

Exhaust air connection	Yes	No
Installation under ventilation system?	<input type="checkbox"/>	<input type="checkbox"/>
Connected to outgoing air duct?	<input type="checkbox"/>	<input type="checkbox"/>
Diameter of the exhaust duct _____ mm (in)		
Length of the exhaust duct _____ mm (in)		

Function check	Yes	No
Set steaming at 90 °C (194 °F). Start cooking process. Device reaches the preset values.	<input type="checkbox"/>	<input type="checkbox"/>
Start the convection heating. Open the cooking chamber door. Does the fan stop if you open the cooking chamber door while the appliance is running?	<input type="checkbox"/>	<input type="checkbox"/>
Unit heated and rinsed?	<input type="checkbox"/>	<input type="checkbox"/>

Final notes	Yes	No
Was the unit put into service?	<input type="checkbox"/>	<input type="checkbox"/>
Comments:		
Operator trained?	<input type="checkbox"/>	<input type="checkbox"/>

Electrical installation was made by:			
Company	Installation fitter	Place, date	Signature

The connection to a kitchen guiding system was made by:			
Company	Installation fitter	Place, date	Signature

The water and sewage installation was carried out by:
---

			Signature
Company	Installation fitter	Place, date	

Exhaust air connection was made by:			
			Signature
Company	Installation fitter	Place, date	

Function check was made by:			
			Signature
Company	Installation fitter	Place, date	

Operator was trained by:			
			Signature
Company	Installation fitter	Place, date	

8.2 Nameplate




Image: Nameplate information

- |                    |                                 |
|--------------------|---------------------------------|
| a Manufacturer     | g Connection pressure for water |
| b Serial number    | h Year of manufacture           |
| c Type number      | i Type of connection            |
| d Protection class | j Electrical connected load     |
| e Frequency        | k Manufacturer's web address    |
| f Barcode          | l Certificate                   |







Henny Penny Corp., Eaton, Ohio 45320, Revised 4/24/2024



Henny Penny Corporation  
P.O.Box 60  
Eaton, OH 45320  
USA

Phone +1 937 456-8400  
Fax +1 937 456-8402

Toll free in USA  
Phone +1 937 417-8417  
Fax +1 937 417-8434

[www.hennypenny.com](http://www.hennypenny.com)