




Remove the plastic cover from the locking mechanism





Remove the plastic cover





Carefully remove the metal cover disc



Now carefully remove the metal spacer




Notice that there are three screws. Remove the three screws using a T-15 torx driver.

It is easiest to remove the top screw first by rotaing the handle to expose the screw head.

Be careful. . . if they drop it can be difficult to retrieve them






The door handle and mechanism can now be removed from the door.




To remove the mechanism first remove the decal. save this for later.



Note the 5mm Allen screw behind the decal.





Remove the 5mm Allen screw




Using the Allen wrench, push out the mechanism.



You should now have the mechanism in your hands





Carefully pull the mechanism apart. There is a spring inside so use caution



All of the door handle parts - this comes as one assembly (MM207092)





Place the black plastic piece onto the "hook" piece.



It will fit only in one position




Now place the spring onto this as shown





Insert the assembly into the housing. Be sure that the spring lines up with the notch in the housing



Carefully rotate the assembly clockwise until the other "pin of the sping lines up with the other notch in the housing.




Slide the assembly into the housing





Now place the complete assembly into the the handle.





Reinstall the screw





Place the handle onto the door and install the bottom two screws first and the top screw last.

Again be careful not to drop the screws. Putty, gum, or some other sticky substance will help you.



Install the metal spacer



Install the cover disc





Install the plastic cover



And the screws



